

FEATURES

- Solid metal construction for durability and reliability
- Two-handle, widespread lavatory faucet for 8" (203 mm) - 16" (406 mm) centers
- Quarter-turn washerless ceramic disc valves
- 1.2 gal/min (4.5 l/min) maximum flow rate
- Includes drain
- Meets CalGreen requirements for lavatory faucets
- Complements the Script collection

CODES/STANDARDS APPLICABLE


P25006

Specified model meets or exceeds the following:

- ADA* (pending)
- ASME A112.18.1/CSA B125.1 (pending)
- CSA B651* (pending)
- EPA WaterSense® (pending)
- ICC/ANSI A117.1 (pending)
- NSF 61 (pending)
- OBC* (pending)
- All applicable US Federal and State material regulations (pending)



* Compliant when installed to the specific requirement of this regulation



SPECIFIED MODEL			
Model	Description	Finishes	
P25006-CR	Script Sink Faucet, Low Spout, Cross Handle	<input type="checkbox"/> CP Polished Chrome	<input type="checkbox"/> AD Nickel Silver
		<input type="checkbox"/> BCH Brushed Cashmere	
P25006-LV	Script Sink Faucet, Low Spout, Lever Handle	<input type="checkbox"/> CP Polished Chrome	<input type="checkbox"/> AD Nickel Silver
		<input type="checkbox"/> BCH Brushed Cashmere	

We reserve the right to make revisions without notice in the design of products or in packaging unless this right has specifically been waived at the time the order is accepted.